


MB-PT1650











SPECIFICATIONS

-1

| Recommended excavator | ton | 19 - 25 |
|-----------------------------------|--------|-----------|
| Main frame weight | ton | 1.235 |
| Ø Maximum Rebar | mm | 40 |
| Speed/Min. (minimum - maximum) | rpm | 20 - 25 |
| Rotation | Degree | 360° |
| Oil pressure (rotation) | bar | 200 - 250 |
| Oil flow rate (rotation) | l/min | 30 - 40 |
| Oil pressure (opening - closing) | bar | 300 - 350 |
| Oil flow rate (opening – closing) | l/min | 100 - 150 |
| Size A | mm | 1865 |
| Size B | mm | 705 |
| Size C | mm | 1390 |
| Size D | mm | 315 |
| Size E | mm | 850 |
| Size G | mm | 288 |
| Size H | | 2010 |

JAW KIT

| KIT | | WEIGHT |
|-------------|-----|-----------|
| , Crusher K | it | 0.435 ton |
| Pulverize | Kit | 0.48 ton |
| Shear Kit | | 0.458 ton |
| | | |

OPTIONAL ACCESSORIES

12 V Electrical Kit (for 2 hose functionality)

24 Month Warranty

APPLICATION AREAS



